



RTU DIGITAL INPUT MODULE TELEM-DI24 T

User Manual

Martem AS
2009

Preface

This document, User Manual edition 1.0 for RTU Digital Input Module TELEM-DI24T version 1.0, provides a general technical description of the module, its configuration and use. Although we have carefully checked the contents of this publication for conformity with the hardware and software described, we cannot guarantee complete conformity since errors cannot be excluded. The information provided in this manual is checked at regular intervals and any corrections that might become necessary are included in the next releases. Any suggestions for improvement are welcome.

The RTU Digital Input Module TELEM-DI24T has been designed and manufactured according to the quality principles of ISO 9001.

TELEM is a registered trademark of MarTem AS.

Contents


1. Application	3
2. Construction.....	3
3. Features.....	4
4. Technical Data	5
5. Mode Switches and Indication LED	5
6. Loading Frame Program	6
6.1 Erase Flash from the Controller.....	6
6.2 To Load a New Frame Program	6
6.3 Load the Frame Program.....	6
7. Configuration.....	7
7.1 Configurable Parameters and General Settings of Communication Ports	7
7.2. Configuration Parameters for Digital Inputs	7
7.3. Logical Operations with Digital Inputs.....	11
8. Connection to Signal Lines.....	12
9. Pin Layouts of Communication Ports	13


1. Application

TELEM-DI24T digital input module is used for digital contact info acquisition, pulse counting and data exchange with higher level devices or systems. Its functionality allows it to be flexibly used for distributed process automation in systems to determine statuses of different objects or as a pulse counter where reliable information acquisition and excellent noise immunity with respect to environmental and electromagnetic influences are important. It may be used as a standalone device or in a daisy chain connection with other modules.

2. Construction

The mechanical design is based on a plastic box that can be readily mounted on 35-mm rails. The module is based on 32 ARM CPU. Interfaces to other equipment are RS-232 or RS-422. Data exchange protocol IEC 60870-5-1-101. Time synchronization is possible with synchronization pulse through a GW6 device.





3. Features


- Time synchronization with 1 ms accuracy
- 2 level input filters - buffer depth for each time-tagged input is 20
- Logical operations with inputs
- Leased line or a dial-up mode operation, data GSM communication request by an event in substation or by the remote control centre
- Configuration / parameterization with IEC protocol at the same line with data communication
- Daisy chain master – slave connection of up to 15 same type of modules using RS-422 interface and up to 45 different type of modules
- Self diagnostics and supervision simultaneously with data acquisition

4. Technical Data

Number of digital inputs	24
Indication	1 for every input, 1 for a running indication, 1 for an alert indication
Built-in clock with a backup capacitor	Yes
Supply voltage	9-30 V DC, 4 W
Isolated input circuit voltage for signal circuits	48V DC, 20 VA; 110V DC 50VA (optional)
Weight	495 g
Mounting	DIN 35
Dimensions (WxHxD)	250 x 120 x 60
Terminals for signal	MVSTBWA 2,5/4-ST
Terminal for power	MVSTBWA 2,5/4-ST
Terminal for communication	RJ4/4 (RS232); RJ12 (RS422)
Over voltage protection	IEC-60255-4, 5 kV pulse protection IEC-60255-5, 2 kV DC on
Disturbance	IEC-61000-3-2, 61000-6-2, 6100-6-4
Ambient temperature in operation	-20...+50°C

5. Mode Switches and Indication LED

Mode of operation, address of the module and the default settings are determined using switches on the board



RST – ON - reset the device
DFT - ON- restores the default setup after a reset
A0 - A3 - determines the address of the module in binary



ERASE - ON erases the frame program (**be careful!**)
PROG - ON loads a new frame program

Indication LEDs display the state of the device:

ALERT - fired, error state

RUN – blinking fire/unfired 1/1, normal operation and synchronized by an internal clock,
RUN – blinking fired/unfired 1/9, normal operation and synchronized by a gateway.

SIGNAL STATE - green fired, signal is activated, polarity of signal voltage normal,
SIGNAL STATE- red fired, signal is activated, polarity of signal voltage inversed.

6. Loading Frame Program

6.1 Erase Flash from the Controller

- 1) switch ERASE to ON state
- 2) wait 2 seconds
- 3) switch RST to ON state
- 4) switch ERASE to OFF state
- 5) switch PROG to ON state
- 6) switch RST to OFF state
- 7) wait 5 seconds
- 8) switch RST to ON state
- 9) switch PROG to OFF state
- 10) switch RST to OFF state

6.2 To Load a New Frame Program

- 1) switch ERASE to ON/OFF state
- 2) switch PROG to ON state
- 3) load a new program
- 4) switch PROG to OFF state
- 5) switch DFT to ON state
- 6) switch RST ON/OFF
- 7) switch DFT to OFF state

6.3 Load the Frame Program

- 1) Download the SAM-BA.exe host program (AT91 In-system Programmer). The program can be downloaded from:
http://www.atmel.com/dyn/products/tools_card.asp?tool_id=3883
- 2) Specify the COM port, location of the SAM-BA core files and the “rtu_arm_di_501.bin” file
- 3) Run “rtu_5_di_programming.bat”

7. Configuration

TELEM-DI24-T is configured using **TELEM 2000** software. All 24 digital inputs are configured independently.

7.1 Configurable Parameters and General Settings of Communication Ports

• Transmission rate	200...38400 bit/s
• Communication mode	asynchronous data bits 8, parity N, stop bits 1
• Communication interface	RS232, selectable RS422 or RS485
• Communication protocol	IEC60870-5-101 slave/master, unbalanced
• Link address length	1 byte
• ASDU address length	2 byte
• Object address length	2 byte
• GPS time synchronization input	9600 bps (RS422/485 RX),
• Time synchronization protocol	ASCII (Motorola), device TLM- optically to 2,5kV RMS
• Communication interface isolation	

7.2. Configuration Parameters for Digital Inputs

TELEM DI24T module is configurable by Telem-2000 RTU configuration software or by other configuration software using the data exchange protocol IEC60870-5-101. Telem-2000 RTU configuration software runs under Windows 95 or later operating systems on any standard PC, communicates via COM interface and performs the following principal functions:

- Configuration / parameterization of telecontrol substations
- Back up of RTU configuration data

Configuration of Telem controllers

- No. of controller (look at Settings/Channels and controllers)

Common parameters

Obj. base address: Disable time sync. by protocol

Comm. speed: Parity: **(Loaded parameters are activated after Reset w [Cancel])**

Type/version: **DI 5.01** ...

Digital inp.

Inputs				Inp./Form.		Debouncing filter		Chatter filter		
No.	In use (Y/N)	Type	Time tag	Tolerant ph.	Intolerant ph.	No.of times	Base time	Lock-out per.mp.	Count. deadb.	
1	0 - In use	1 - Double	0 - Yes	0	0	0 0		0	0	
2	0 - In use	0 - Single	0 - Yes	0	5000	0	0	0	0	
3	0 - In use	1 - Double	0 - Yes	0	0	0	0	0	0	
4	0 - In use	0 - Single	0 - Yes	0	5000	0	0	0	0	
5	0 - In use	0 - Single	0 - Yes	0	0	0	0	0	0	
6	0 - In use	0 - Single	0 - Yes	0	5000	0	0	0	0	
7	0 - In use	0 - Single	0 - Yes	0	500	0	0	0	0	
8	0 - In use	0 - Single	0 - Yes	0	0	0	0	0	0	
9	0 - In use	0 - Single	0 - Yes	0	0	0	0	0	0	
10	0 - In use	0 - Single	0 - Yes	0	0	0	0	0	0	
11	0 - In use	0 - Single	0 - Yes	0	0	0	0	0	0	
12	0 - In use	0 - Single	0 - Yes	0	0	0	0	0	0	

Parameters of all types are read **(Loaded parameters are activated after Reset with code 1)**

...

TELEM-DI24T configuration tab card


Parameter	Value	Default value
General		
1. In use	Yes No	Yes
2. Single- or double signal or counter input [In case of double signal the next input is used for second signal]	Single Double	Single
3. Time tagged	Yes No	Yes
Debouncing filter		
4. Tolerant phase [A period of time during which changes of state are permitted and ignored on a digital input signal]	1-255 ms.	5 ms (0)
5. Intolerant phase [A period of time during which the state of a digital input must remain constant]	1-255 ms.	5 ms (0)
Chatter filter		
[A facility that is used to disable a digital input point if the number of state changes of that point is excessively high during a defined time interval]		
6. Chatter times [changes]	1-255 times	5 (0)
7. Filter base [defined time interval]	0-32000 ms.	500 ms (0)
8. Lock-out period multiplier [Number of filter base periods when the chatter filter will be on]	1-255 periods	1
Counter		
9. Number of pulses for creating an event [Counter event is always without time tag]	1-255 pulses	100 (0)

Digital input processing

Debouncing filter

Tolerant phase: A period of time during which contact bounce is “acceptable”. Having a tolerant period allows you to monitor and time-stamp the initial state of change while ignoring any subsequent contact bounces.

Intolerant phase: A period of time following the tolerant phase during which contact bounce is not “acceptable”. It ensures that contact bounce is not mistaken for a valid change of state.




Chatter filter


Chatter times (changes): The maximum allowed number of state transitions that can occur within a filter base period. If the number of state transitions during a filter period equals or exceeds the maximum allowed number of state transitions, chatter filter will turn ON and any further transitions will be ignored for the duration of the “lock-out” period.

Lock-out period: The minimum number of filter base periods during which the chatter filter will remain ON. The chatter filter can proceed from ON to OFF only if no state transitions are detected during the entire lock-out period.

Example: Chatter times (changes) 5, Lock-out period 1



7.3. Logical Operations with Digital Inputs



TELEM-DI24T Formulas Tab Card

It is possible to configure formulas where inputs are combined with NOT, AND, OR and XOR operations.

When formulas are used, every formula occupies one IEC protocol object address of inputs (substitutes the input).

By their default, IEC objects and inputs are bound with the following formulas:

$$Y_1 = X_1$$


$$Y_2 = X_2$$

... $Y_{24} = X_{24}$ Where X is input and Y is the calculated value.

8. Connection to Signal Lines

Layout of the terminals of digital input signals


X1



9. Pin Layouts of Communication Ports

Port 1

RJ 11/4



Port 2 and 3

RJ 12/6

